



PRIME's Mini-Dome, is a True Day/Night network camera that provides 720P or 1080P full HD resolution for high quality images. H264 and MJPEG video compression provides excellent image clarity, and efficient bandwidth and video storage. Featuring built-in IR illuminators, the Mini-Dome produces clear images at an effective distance up to 25 meters in a variety of low light conditions. For different applications, we provide choices of different lens options from fixed, vari-focal and motorized vari-focal (remote-zoom/remote-focus). Also come with "Tampering Alarm" to prevent tampering from anyone who are trying to stop being "watched" by covering the camera's view.



## PRIME'S MINIDOME CAMERA

INFRA-RED ENABLED, INDOOR HD CAMERA

### HIGHLIGHTS

- Offer resolution from 720P to 1080P
- WDR feature to generate clear image with shade and brightness happened
- True Day/Night function with mechanical IR cut filter
- Multiple Lens option - fixed focal, vari-focal and motorized vari-focal (remote-zoom/remote-focus)
- Infra-Red LED allows surveillance under NO light up to 25 meters
- Advanced 3D noise reduction
- Motion detection and privacy mask function
- Quad-streaming
- Bi-directional audio
- Onboard storage - microSD support



## Camera Imaging Specifications

Model	PMD2113DN -xxxxx	PMD2120DN -xxxxx	PMD2130DN -xxxxx
Video Compression	H.264/MJPEG		
Image Sensor & Resolution	1/2.5" CMOS 1280x720@30FPS	1/2.5" CMOS 1920x1080@30FPS	1/2.8" Sony CMOS 2048x1536@15FPS
True Day/Night	Mechanical IR Cut Filter		
Minimum Illumination	Color 0.2 lux / Black and white 0.02 Lux		
Lens Option	Fixed focal Lens product code suffix -F028: 2.8mm F1.2 / -F036: 3.6mm F1.2 Vari-focal Lens -V0390: 3-9mm F1.2 / -V2812: 2.8-12mm F1.2 Motorized Vari-focal Lens -M0390: 3-9mm F1.4		
Dual Streaming	Main streaming: 1280x720		Main streaming: 1920x1080
	Sub-streaming: 704x576 / 352x288		

## Network

Interface	RJ-45 connector, 10/100mbps
Video Streaming	Dual Streams H.264 + H.264 / H.264 + MJPEG Quad Streams H.264 x 4 / H.264 x 3 + MJPEG
Frame Rate	Dual Streams : 1080p (30/25 fps) + D1 (30/25 fps)
Protocol	ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Security/Authorization	HTTPS / IP Filter / IEEE 802.1X
Audio	Line in/Line out, G.711/G.726
Alarm Input/Output	Input x 1 / Output x 1
Event Notification	HTTP / FTP / SMTP
Onboard Storage	microSDHC 32GB support
Supported Web Browser	Internet Explorer (6.0+) / Chrome / Firefox / Safari
Users / Password	20 User accounts / User & Administrator

## General

Operating Temperature	-10°C ~ 50°C (14° ~ 122° F)
Humidity	10% ~ 90%, No Condensation
Dimension	ø 117 x 90 mm (ø 4.6 x 3.6 in. )
Weight	280 g
Power Source	PoE / DC 12V / AC 24 V
Regulatory	FCC / EMC / LVD / RoHS

## Built-in IR Illuminator (Optional)

Product Code	Add Suffix: -IR
Working Dist.	Up to 25m
Wavelength	850nm
Number of LEDs	24